

---

**darc**

***Release 0.6.0***

**Jarry Shaw**

**Nov 21, 2020**



# CONTENTS

<b>1 Darkweb Crawler Project</b>	<b>1</b>
1.1 URL Utilities . . . . .	1
1.2 Proxy Utilities . . . . .	6
1.3 Sites Customisation . . . . .	13
1.4 Module Constants . . . . .	15
1.5 Custom Exceptions . . . . .	20
<b>2 Docker Integration</b>	<b>23</b>
<b>3 Web Backend Demo</b>	<b>35</b>
<b>4 Data Models Demo</b>	<b>41</b>
<b>5 Auxiliary Scripts</b>	<b>45</b>
5.1 Health Check . . . . .	45
5.2 Upload API Submission Files . . . . .	45
5.3 Remove Repeated Lines . . . . .	46
<b>6 Installation</b>	<b>49</b>
<b>7 Usage</b>	<b>51</b>
<b>8 Configuration</b>	<b>53</b>
8.1 General Configurations . . . . .	53
8.2 Data Storage . . . . .	54
8.3 Web Crawlers . . . . .	56
8.4 White / Black Lists . . . . .	57
8.5 Data Submission . . . . .	59
8.6 Tor Proxy Configuration . . . . .	60
8.7 I2P Proxy Configuration . . . . .	61
8.8 ZeroNet Proxy Configuration . . . . .	62
8.9 Freenet Proxy Configuration . . . . .	63
<b>9 Indices and tables</b>	<b>65</b>
<b>Python Module Index</b>	<b>67</b>
<b>Index</b>	<b>69</b>



## DARKWEB CRAWLER PROJECT

`darc` is designed as a swiss army knife for darkweb crawling. It integrates `requests` to collect HTTP request and response information, such as cookies, header fields, etc. It also bundles `selenium` to provide a fully rendered web page and screenshot of such view.

### 1.1 URL Utilities

The `Link` class is the key data structure of the `darc` project, it contains all information required to identify a URL's proxy type, hostname, path prefix when saving, etc.

The `link` module also provides several wrapper function to the `urllib.parse` module.

**class** `darc.link.Link(url, proxy, url_parse, host, base, name)`  
Bases: `object`

Parsed link.

#### Parameters

- `url` – original link
- `proxy` – proxy type
- `host` – URL's hostname
- `base` – base folder for saving files
- `name` – hashed link for saving files
- `url_parse` – parsed URL from `urllib.parse.urlparse()`

**Returns** Parsed link object.

**Return type** `Link`

---

**Note:** `Link` is a dataclass object. It is safely *hashable*, through `hash(url)`.

---

#### `__hash__()`

Provide hash support to the `Link` object.

**base:** `str`

base folder for saving files

**host:** `str`

URL's hostname

```
name: str
    hashed link for saving files

proxy: str
    proxy type

url: str
    original link

url_parse: urllib.parse.ParseResult
    parsed URL from urllib.parse.urlparse()

darc.link.parse_link(link, host=None)
Parse link.
```

#### Parameters

- **link** (`str`) – link to be parsed
- **host** (*Optional*[`str`]) – hostname of the link

**Returns** The parsed link object.

**Return type** `darc.link.Link`

---

**Note:** If `host` is provided, it will override the hostname of the original link.

---

The parsing process of proxy type is as follows:

0. If `host` is `None` and the parse result from `urllib.parse.urlparse()` has no netloc (or hostname) specified, then set hostname as `(null)`; else set it as is.
1. If the scheme is `data`, then the link is a data URI, set hostname as `data` and proxy as `data`.
2. If the scheme is `javascript`, then the link is some JavaScript codes, set proxy as `script`.
3. If the scheme is `bitcoin`, then the link is a Bitcoin address, set proxy as `bitcoin`.
4. If the scheme is `ed2k`, then the link is an ED2K magnet link, set proxy as `ed2k`.
5. If the scheme is `magnet`, then the link is a magnet link, set proxy as `magnet`.
6. If the scheme is `mailto`, then the link is an email address, set proxy as `mail`.
7. If the scheme is `irc`, then the link is an IRC link, set proxy as `irc`.
8. If the scheme is **NOT** any of `http` or `https`, then set proxy to the scheme.
9. If the host is `None`, set hostname to `(null)`, set proxy to `null`.
10. If the host is an onion (`.onion`) address, set proxy to `tor`.
11. If the host is an I2P (`.i2p`) address, or any of `localhost:7657` and `localhost:7658`, set proxy to `i2p`.
12. If the host is `localhost` on `ZERONET_PORT`, and the path is not `/`, i.e. **NOT** root path, set proxy to `zeronet`; and set the first part of its path as hostname.

Example:

For a ZeroNet address, e.g. `http://127.0.0.1:43110/1HeLlo4uzjaLetFx6NH3PMwFP3qbRbTf3D`, `parse_link()` will parse the hostname as `1HeLlo4uzjaLetFx6NH3PMwFP3qbRbTf3D`.

13. If the host is *localhost* on *FREENET\_PORT*, and the path is not /, i.e. **NOT** root path, set proxy to freenet; and set the first part of its path as hostname.

Example:

For a Freenet address, e.g. http://127.0.0.1:8888/USK@nwa8lHa271k2QvJ8aa0Ov7IHAV-DFOCFgmDt3X6BpCI,DuQSUZiI~agF8c-6tjsFFGuZ8eICrzWCILB60nT8KKo, AQACAAE/sone/77/, `parse_link()` will parse the hostname as USK@nwa8lHa271k2QvJ8aa0Ov7IHAV-DFOCFgmDt3X6BpCI, DuQSUZiI~agF8c-6tjsFFGuZ8eICrzWCILB60nT8KKo, AQACAAE.

14. If none of the cases above satisfied, the proxy will be set as null, marking it a plain normal link.

The base for parsed link `Link` object is defined as

```
<root>/<proxy>/<scheme>/<hostname>/
```

where `root` is `PATH_DB`.

The name for parsed link `Link` object is the sha256 hash (c.f. `hashlib.sha256()`) of the original link.

`darc.link.quote(string, safe='/', encoding=None, errors=None)`

Wrapper function for `urllib.parse.quote()`.

#### Parameters

- **string** (`AnyStr`) – string to be quoted
- **safe** (`AnyStr`) – characters not to escape
- **encoding** (`Optional[str]`) – string encoding
- **errors** (`Optional[str]`) – encoding error handler

**Returns** The quoted string.

**Return type** `str`

---

**Note:** The function suppressed possible errors when calling `urllib.parse.quote()`. If any, it will return the original string.

`darc.link.unquote(string, encoding='utf-8', errors='replace')`

Wrapper function for `urllib.parse.unquote()`.

#### Parameters

- **string** (`AnyStr`) – string to be unquoted
- **encoding** (`str`) – string encoding
- **errors** (`str`) – encoding error handler

**Returns** The quoted string.

**Return type** `str`

---

**Note:** The function suppressed possible errors when calling `urllib.parse.unquote()`. If any, it will return the original string.

`darc.link.urljoin(base, url, allow_fragments=True)`

Wrapper function for `urllib.parse.urljoin()`.

### Parameters

- **base** (*AnyStr*) – base URL
- **url** (*AnyStr*) – URL to be joined
- **allow\_fragments** (*bool*) – if allow fragments

**Returns** The joined URL.

**Return type** `str`

---

**Note:** The function suppressed possible errors when calling `urllib.parse.urljoin()`. If any, it will return `base/url` directly.

---

`darc.link.urlparse(url, scheme='', allow_fragments=True)`

Wrapper function for `urllib.parse.urlparse()`.

### Parameters

- **url** (*str*) – URL to be parsed
- **scheme** (*str*) – URL scheme
- **allow\_fragments** (*bool*) – if allow fragments

**Returns** The parse result.

**Return type** `urllib.parse.ParseResult`

---

**Note:** The function suppressed possible errors when calling `urllib.parse.urlparse()`. If any, it will return `urllib.parse.ParseResult(scheme=scheme, netloc='', path=url, params='', query='', fragment='')` directly.

---

`darc.save._SAVE_LOCK: Union[multiprocessing.Lock, threading.Lock, contextlib.nullcontext]`  
I/O lock for saving link hash database `link.csv`.

**See also:**

- `darc.save.save_link()`
- `darc.const.get_lock()`

`darc.db.BULK_SIZE: int`

**Default** 100

**Environ** `DARC_BULK_SIZE`

*Bulk* size for updating Redis databases.

**See also:**

- `darc.db.save_requests()`
- `darc.db.save_selenium()`

`darc.db.LOCK_TIMEOUT: Optional[float]`

**Default** 10

**Environ** `DARC_LOCK_TIMEOUT`

Lock blocking timeout.

---

**Note:** If is an infinit `inf`, no timeout will be applied.

---

**See also:**

Get a lock from `darc.db.get_lock()`.

`darc.db.MAX_POOL: int`

**Default** `1_000`

**Environ** `DARC_MAX_POOL`

Maximum number of links loading from the database.

---

**Note:** If is an infinit `inf`, no limit will be applied.

---

`darc.db.REDIS_LOCK: bool`

**Default** `False`

**Environ** `DARC_REDIS_LOCK`

If use Redis (Lua) lock to ensure process/thread-safely operations.

**See also:**

Toggles the behaviour of `darc.db.get_lock()`.

`darc.db.REDIS_RETRY: int`

**Default** `10`

**Environ** `DARC_REDIS_RETRY`

Retry interval between each Redis command failure.

---

**Note:** If is an infinit `inf`, no interval will be applied.

---

**See also:**

Toggles the behaviour of `darc.db.redis_command()`.

`darc.submit.PATH_API = '{PATH_DB}/api/'`

Path to the API submittion records, i.e. `api` folder under the root of data storage.

**See also:**

- `darc.const.PATH_DB`

`darc.submit.SAVE_DB: bool`

Save submitted data to database.

**Default** `True`

**Environ** `SAVE_DB`

`darc.submit.API_RETRY: int`

Retry times for API submission when failure.

**Default** 3

**Environ** `API_RETRY`

`darc.submit.API_NEW_HOST: str`  
API URL for `submit_new_host()`.

**Default** `None`

**Environ** `API_NEW_HOST`

`darc.submit.API_REQUESTS: str`  
API URL for `submit_requests()`.

**Default** `None`

**Environ** `API_REQUESTS`

`darc.submit.API_SELENIUM: str`  
API URL for `submit_selenium()`.

**Default** `None`

**Environ** `API_SELENIUM`

---

**Note:** If `API_NEW_HOST`, `API_REQUESTS` and `API_SELENIUM` is `None`, the corresponding submit function will save the JSON data in the path specified by `PATH_API`.

---

**See also:**

The `darc` provides a demo on how to implement a `darc`-compliant web backend for the data submission module. See the `demo` page for more information.

## 1.2 Proxy Utilities

The `darc.proxy` module provides various proxy support to the `darc` project.

`darc.proxy.bitcoin.PATH = '{PATH_MISC}/bitcoin.txt'`  
Path to the data storage of bitcoin addresses.

**See also:**

- `darc.const.PATH_MISC`

`darc.proxy.bitcoin.LOCK: Union[multiprocessing.Lock, threading.Lock, contextlib.nullcontext]`  
I/O lock for saving bitcoin addresses `PATH`.

**See also:**

- `darc.const.get_lock()`

`darc.proxy.data.PATH = '{PATH_MISC}/data/'`  
Path to the data storage of data URI schemes.

**See also:**

- `darc.const.PATH_MISC`

---

`darc.proxy.ed2k.PATH = '{PATH_MISC}/ed2k.txt'`  
Path to the data storage of bED2K magnet links.

**See also:**

- `darc.const.PATH_MISC`

`darc.proxy.ed2k.LOCK: Union[multiprocessing.Lock, threading.Lock, contextlib.nullcontext]`  
I/O lock for saving ED2K magnet links `PATH`.

**See also:**

- `darc.const.get_lock()`

The following constants are configuration through environment variables:

`darc.proxy.freenet.FREENET_PORT: int`  
Port for Freenet proxy connection.

**Default** 8888

**Environ** `FREENET_PORT`

`darc.proxy.freenet.FREENET_RETRY: int`  
Retry times for Freenet bootstrap when failure.

**Default** 3

**Environ** `FREENET_RETRY`

`darc.proxy.freenet.BS_WAIT: float`  
Time after which the attempt to start Freenet is aborted.

**Default** 90

**Environ** `FREENET_WAIT`

---

**Note:** If not provided, there will be **NO** timeouts.

---

`darc.proxy.freenet.FREENET_PATH: str`  
Path to the Freenet project.

**Default** /usr/local/src/freenet

**Environ** `FREENET_PATH`

`darc.proxy.freenet.FREENET_ARGS: List[str]`  
Freenet bootstrap arguments for run.sh start.

If provided, it should be parsed as command line arguments (c.f. `shlex.split()`).

**Default** ''

**Environ** `FREENET_ARGS`

---

**Note:** The command will be run as `DARC_USER`, if current user (c.f. `getpass.getuser()`) is `root`.

---

The following constants are defined for internal usage:

`darc.proxy.freenet._MNG_FREENET: bool`  
If manage Freenet proxy through `darc`.

**Default** `True`

**Environ** `DARC_FREENET`

`darc.proxy.freenet._FREENET_BS_FLAG: bool`

If the Freenet proxy is bootstrapped.

`darc.proxy.freenet._FREENET_PROC: subprocess.Popen`

Freenet proxy process running in the background.

`darc.proxy.freenet._FREENET_ARGS: List[str]`

Freenet proxy bootstrap arguments.

`darc.proxy.i2p.I2P_REQUESTS_PROXY: Dict[str, Any]`

Proxy for I2P sessions.

**See also:**

- `darc.requests.i2p_session()`

`darc.proxy.i2p.I2P_SELENIUM_PROXY: selenium.webdriver.common.proxy.Proxy`

Proxy for I2P web drivers.

**See also:**

- `darc.selenium.i2p_driver()`

The following constants are configuration through environment variables:

`darc.proxy.i2p.I2P_PORT: int`

Port for I2P proxy connection.

**Default** `4444`

**Environ** `I2P_PORT`

`darc.proxy.i2p.I2P_RETRY: int`

Retry times for I2P bootstrap when failure.

**Default** `3`

**Environ** `I2P_RETRY`

`darc.proxy.i2p.BS_WAIT: float`

Time after which the attempt to start I2P is aborted.

**Default** `90`

**Environ** `I2P_WAIT`

---

**Note:** If not provided, there will be **NO** timeouts.

---

`darc.proxy.i2p.I2P_ARGS: List[str]`

I2P bootstrap arguments for i2prouter start.

If provided, it should be parsed as command line arguments (c.f. `shlex.split()`).

**Default** `''`

**Environ** `I2P_ARGS`

---

**Note:** The command will be run as `DARC_USER`, if current user (c.f. `getpass.getuser()`) is `root`.

---

The following constants are defined for internal usage:

`darc.proxy.i2p._MNG_I2P: bool`

If manage I2P proxy through `darc`.

**Default** `True`

**Environ** `DARC_I2P`

`darc.proxy.i2p._I2P_BS_FLAG: bool`

If the I2P proxy is bootstrapped.

`darc.proxy.i2p._I2P_PROC: subprocess.Popen`

I2P proxy process running in the background.

`darc.proxy.i2p._I2P_ARGS: List[str]`

I2P proxy bootstrap arguments.

`darc.proxy.irc.PATH = '{PATH_MISC}/irc.txt'`

Path to the data storage of IRC addresses.

**See also:**

- `darc.const.PATH_MISC`

`darc.proxy.irc.LOCK: Union[multiprocessing.Lock, threading.Lock, contextlib.nullcontext]`

I/O lock for saving IRC addresses `PATH`.

**See also:**

- `darc.const.get_lock()`

`darc.proxy.magnet.PATH = '{PATH_MISC}/magnet.txt'`

Path to the data storage of magnet links.

**See also:**

- `darc.const.PATH_MISC`

`darc.proxy.magnet.LOCK: Union[multiprocessing.Lock, threading.Lock, contextlib.nullcontext]`

I/O lock for saving magnet links `PATH`.

**See also:**

- `darc.const.get_lock()`

`darc.proxy.mail.PATH = '{PATH_MISC}/mail.txt'`

Path to the data storage of email addresses.

**See also:**

- `darc.const.PATH_MISC`

`darc.proxy.mail.LOCK: Union[multiprocessing.Lock, threading.Lock, contextlib.nullcontext]`

I/O lock for saving email addresses `PATH`.

**See also:**

- `darc.const.get_lock()`

`darc.proxy.null.PATH = '{PATH_MISC}/invalid.txt'`

Path to the data storage of links with invalid scheme.

See also:

- `darc.const(PATH_MISC)`

`darc.proxy.null.LOCK: Union[multiprocessing.Lock, threading.Lock, contextlib.nullcontext]`

I/O lock for saving links with invalid scheme `PATH`.

See also:

- `darc.const.get_lock()`

`darc.proxy.script.PATH = '{PATH_MISC}/script.txt'`

Path to the data storage of bitcoin addresses.

See also:

- `darc.const(PATH_MISC)`

`darc.proxy.script.LOCK: Union[multiprocessing.Lock, threading.Lock, contextlib.nullcontext]`

I/O lock for saving JavaScript links `PATH`.

See also:

- `darc.const.get_lock()`

`darc.proxy.tel.PATH = '{PATH_MISC}/tel.txt'`

Path to the data storage of bitcoin addresses.

See also:

- `darc.const(PATH_MISC)`

`darc.proxy.tel.LOCK: Union[multiprocessing.Lock, threading.Lock, contextlib.nullcontext]`

I/O lock for saving telephone numbers `PATH`.

See also:

- `darc.const.get_lock()`

`darc.proxy.tor.TOR_REQUESTS_PROXY: Dict[str, Any]`

Proxy for Tor sessions.

See also:

- `darc.requests.tor_session()`

`darc.proxy.tor.TOR_SELENIUM_PROXY: selenium.webdriver.common.proxy.Proxy`

Proxy for Tor web drivers.

See also:

- `darc.selenium.tor_driver()`

---

The following constants are configuration through environment variables:

`darc.proxy.tor.TOR_PORT: int`

Port for Tor proxy connection.

**Default** 9050

**Environ** `TOR_PORT`

`darc.proxy.tor.TOR_CTRL: int`

Port for Tor controller connection.

**Default** 9051

**Environ** `TOR_CTRL`

`darc.proxy.tor.TOR_PASS: str`

Tor controller authentication token.

**Default** `None`

**Environ** `TOR_PASS`

---

**Note:** If not provided, it will be requested at runtime.

`darc.proxy.tor.TOR_RETRY: int`

Retry times for Tor bootstrap when failure.

**Default** 3

**Environ** `TOR_RETRY`

`darc.proxy.tor.BS_WAIT: float`

Time after which the attempt to start Tor is aborted.

**Default** 90

**Environ** `TOR_WAIT`

---

**Note:** If not provided, there will be **NO** timeouts.

`darc.proxy.tor.TOR_CFG: Dict[str, Any]`

Tor bootstrap configuration for `stem.process.launch_tor_with_config()`.

**Default** `{}`

**Environ** `TOR_CFG`

---

**Note:** If provided, it will be parsed from a JSON encoded string.

The following constants are defined for internal usage:

`darc.proxy.tor._MNG_TOR: bool`

If manage Tor proxy through `darc`.

**Default** `True`

**Environ** `DARC_TOR`

`darc.proxy.tor._TOR_BS_FLAG: bool`

If the Tor proxy is bootstrapped.

```
darc.proxy.tor._TOR_PROC: subprocess.Popen
    Tor proxy process running in the background.

darc.proxy.tor._TOR_CTRL: stem.control.Controller
    Tor controller process (stem.control.Controller) running in the background.

darc.proxy.tor._TOR_CONFIG: List[str]
    Tor bootstrap configuration for stem.process.launch_tor_with_config().
```

The following constants are configuration through environment variables:

```
darc.proxy.zeronet.ZERONET_PORT: int
    Port for ZeroNet proxy connection.
```

**Default** 43110

**Environ** `ZERONET_PORT`

```
darc.proxy.zeronet.ZERONET_RETRY: int
    Retry times for ZeroNet bootstrap when failure.
```

**Default** 3

**Environ** `ZERONET_RETRY`

```
darc.proxy.zeronet.BS_WAIT: float
    Time after which the attempt to start ZeroNet is aborted.
```

**Default** 90

**Environ** `ZERONET_WAIT`

---

**Note:** If not provided, there will be **NO** timeouts.

---

```
darc.proxy.zeronet.ZERONET_PATH: str
    Path to the ZeroNet project.
```

**Default** /usr/local/src/zeronet

**Environ** `ZERONET_PATH`

```
darc.proxy.zeronet.ZERONET_ARGS: List[str]
    ZeroNet bootstrap arguments for run.sh start.
```

If provided, it should be parsed as command line arguments (c.f. `shlex.split()`).

**Default** ''

**Environ** `ZERONET_ARGS`

---

**Note:** The command will be run as `DARC_USER`, if current user (c.f. `getpass.getuser()`) is *root*.

---

The following constants are defined for internal usage:

```
darc.proxy.zeronet._MNG_ZERONET: bool
    If manage ZeroNet proxy through darc.
```

**Default** True

**Environ** DARC\_ZERONET

```
darc.proxy.zeronet._ZERONET_BS_FLAG: bool
    If the ZeroNet proxy is bootstrapped.
```

`darc.proxy.zeronet._ZERONET_PROC: subprocess.Popen`  
ZeroNet proxy process running in the background.

`darc.proxy.zeronet._ZERONET_ARGS: List[str]`  
ZeroNet proxy bootstrap arguments.

To tell the `darc` project which proxy settings to be used for the `requests.Session` objects and `WebDriver` objects, you can specify such information in the `darc.proxy.LINK_MAP` mapping dictionary.

`darc.proxy.LINK_MAP: DefaultDict[str, Tuple[types.FunctionType, types.FunctionType]]`

```
LINK_MAP = collections.defaultdict(
    lambda: (darc.requests.null_session, darc.selenium.null_driver),
    dict(
        tor=(darc.requests.tor_session, darc.selenium.tor_driver),
        i2p=(darc.requests.i2p_session, darc.selenium.i2p_driver),
    )
)
```

The mapping dictionary for proxy type to its corresponding `requests.Session` factory function and `WebDriver` factory function.

The fallback value is the no proxy `requests.Session` object (`null_session()`) and `WebDriver` object (`null_driver()`).

#### See also:

- `darc.requests` – `requests.Session` factory functions
- `darc.selenium` – `WebDriver` factory functions

## 1.3 Sites Customisation

As websites may have authentication requirements, etc., over its content, the `darc.sites` module provides sites customisation hooks to both `requests` and `selenium` crawling processes.

```
# -*- coding: utf-8 -*-
"""Default Hooks
=====

The :mod:`darc.sites.default` module is the fallback for sites
customisation.

"""

import time

import darc.typing as typing
from darc.const import SE_WAIT
from darc.link import Link


def crawler(session: typing.Session, link: Link) -> typing.Response:
    """Default crawler hook.

Args:

```

(continues on next page)

(continued from previous page)

```
session (requests.Session): Session object with proxy settings.
link: Link object to be crawled.

>Returns:
    requests.Response: The final response object with crawled data.

See Also:
    * :func:`darc.crawl.crawler`


"""
response = session.get(link.url, allow_redirects=True)
return response


def loader(driver: typing.Driver, link: Link) -> typing.Driver:
    """Default loader hook.

    When loading, if :data:`~darc.const.SE_WAIT` is a valid time lapse,
    the function will sleep for such time to wait for the page to finish
    loading contents.

    Args:
        driver (selenium.webdriver.Chrome): Web driver object with proxy settings.
        link: Link object to be loaded.

    Returns:
        selenium.webdriver.Chrome: The web driver object with loaded data.

    Note:
        Internally, :mod:`selenium` will wait for the browser to finish
        loading the pages before return (i.e. the web API event
        |event|_). However, some extra scripts may take more time
        running after the event.

        .. |event| replace:: ``DOMContentLoaded``
        .. _event: https://developer.mozilla.org/en-US/docs/Web/API/Window/
        ↪DOMContentLoaded_event

    See Also:
        * :func:`darc.crawl.loader`
        * :data:`darc.const.SE_WAIT`


"""
driver.get(link.url)

# wait for page to finish loading
if SE_WAIT is not None:
    time.sleep(SE_WAIT)

return driver
```

To customise behaviours over `requests`, you sites customisation module should have a `crawler()` function, e.g. `crawler()`.

The function takes the `requests.Session` object with proxy settings and a `Link` object representing the link to be crawled, then returns a `requests.Response` object containing the final data of the crawling process.

To customise behaviours over `selenium`, you sites customisation module should have a `loader()` function, e.g.

```
loader().
```

The function takes the `WebDriver` object with proxy settings and a `Link` object representing the link to be loaded, then returns the `WebDriver` object containing the final data of the loading process.

To tell the `darc` project which sites customisation module it should use for a certain hostname, you can register such module to the `SITEMAP` mapping dictionary.

`darc.sites.SITEMAP: DefaultDict[str, str]`

```
SITEMAP = collections.defaultdict(lambda: 'default', {
    # 'www.sample.com': 'sample',  # darc.sites.sample
})
```

The mapping dictionary for hostname to sites customisation modules.

The fallback value is `default`, c.f. `darc.sites.default`.

## 1.4 Module Constants

### 1.4.1 Auxiliary Function

`darc.const.get_lock()`

Get a lock.

**Returns** Lock context based on `FLAG_MP` and `FLAG_TH`.

**Return type** Union[multiprocessing.contextBaseContext.Lock, \_thread.allocate\_lock, contextlib.nullcontext]

### 1.4.2 General Configurations

`darc.const.REBOOT: bool`

If exit the program after first round, i.e. crawled all links from the `requests` link database and loaded all links from the `selenium` link database.

This can be useful especially when the capacity is limited and you wish to save some space before continuing next round. See `Docker integration` for more information.

**Default** `False`

**Environ** `DARC_REBOOT`

`darc.const.DEBUG: bool`

If run the program in debugging mode.

**Default** `False`

**Environ** `DARC_DEBUG`

`darc.const.VERBOSE: bool`

If run the program in verbose mode. If `DEBUG` is `True`, then the verbose mode will be always enabled.

**Default** `False`

**Environ** `DARC_VERBOSE`

`darc.const.FORCE: bool`

If ignore robots.txt rules when crawling (c.f. `crawler()`).

**Default** `False`

**Environ** `DARC_FORCE`

`darc.const.CHECK: bool`

If check proxy and hostname before crawling (when calling `extract_links()`, `read_sitemap()` and `read_hosts()`).

If `CHECK_NG` is `True`, then this environment variable will be always set as `True`.

**Default** `False`

**Environ** `DARC_CHECK`

`darc.const.CHECK_NG: bool`

If check content type through `HEAD` requests before crawling (when calling `extract_links()`, `read_sitemap()` and `read_hosts()`).

**Default** `False`

**Environ** `DARC_CHECK_CONTENT_TYPE`

`darc.const.ROOT: str`

The root folder of the project.

`darc.const.CWD = '.'`

The current working direcory.

`darc.const.DARC_CPU: int`

Number of concurrent processes. If not provided, then the number of system CPUs will be used.

**Default** `None`

**Environ** `DARC_CPU`

`darc.const.FLAG_MP: bool`

If enable *multiprocessing* support.

**Default** `True`

**Environ** `DARC_MULTIPROCESSING`

`darc.const.FLAG_TH: bool`

If enable *multithreading* support.

**Default** `False`

**Environ** `DARC_MULTITHREADING`

---

**Note:** `FLAG_MP` and `FLAG_TH` can NOT be toggled at the same time.

---

`darc.const.DARC_USER: str`

*Non-root* user for proxies.

**Default** current login user (c.f. `getpass.getuser()`)

**Environ** `DARC_USER`

### 1.4.3 Data Storage

**See also:**

See `darc.db` for more information about database integration.

`darc.const.REDIS: redis.Redis`

URL to the Redis database.

**Default** `redis://127.0.0.1`

**Environ** `REDIS_URL`

`darc.const.DB: peewee.Database`

URL to the RDS storage.

**Default** `sqlite:///{PATH_DB}/darc.db`

**Environ** `:envvar`DB_URL``

`darc.const.DB: peewee.Database`

URL to the data submission storage.

**Default** `sqlite:///{PATH_DB}/darcweb.db`

**Environ** `:envvar`DB_URL``

`darc.const.FLAG_DB: bool`

Flag if uses RDS as the task queue backend. If `REDIS_URL` is provided, then `False`; else, `True`.

`darc.const.PATH_DB: str`

Path to data storage.

**Default** `data`

**Environ** `PATH_DATA`

**See also:**

See `darc.save` for more information about source saving.

`darc.const.PATH_MISC = '{PATH_DB}/misc/'`

Path to miscellaneous data storage, i.e. `misc` folder under the root of data storage.

**See also:**

- `darc.const.PATH_DB`

`darc.const.PATH_LN = '{PATH_DB}/link.csv'`

Path to the link CSV file, `link.csv`.

**See also:**

- `darc.const.PATH_DB`
- `darc.save.save_link`

`darc.const.PATH_ID = '{PATH_DB}/darc.pid'`

Path to the process ID file, `darc.pid`.

**See also:**

- `darc.const.PATH_DB`
- `darc.const.getpid()`

#### 1.4.4 Web Crawlers

`darc.const.DARC_WAIT: Optional[float]`

Time interval between each round when the `requests` and/or selenium database are empty.

**Default** 60

**Environ** `DARC_WAIT`

`darc.const.TIME_CACHE: float`

Time delta for caches in seconds.

The `darc` project supports *caching* for fetched files. `TIME_CACHE` will specify for how long the fetched files will be cached and **NOT** fetched again.

---

**Note:** If `TIME_CACHE` is `None` then caching will be marked as *forever*.

---

**Default** 60

**Environ** `TIME_CACHE`

`darc.const.SE_WAIT: float`

Time to wait for selenium to finish loading pages.

---

**Note:** Internally, selenium will wait for the browser to finish loading the pages before return (i.e. the web API event `DOMContentLoaded`). However, some extra scripts may take more time running after the event.

---

**Default** 60

**Environ** `SE_WAIT`

`darc.const.SE_EMPTY = '<html><head></head><body></body></html>'`

The empty page from selenium.

**See also:**

- `darc.crawl.loader()`

#### 1.4.5 White / Black Lists

`darc.const.LINK_WHITE_LIST: List[re.Pattern]`

White list of hostnames should be crawled.

**Default** []

**Environ** `LINK_WHITE_LIST`

---

**Note:** Regular expressions are supported.

---

`darc.const.LINK_BLACK_LIST: List[re.Pattern]`

Black list of hostnames should be crawled.

**Default** []

**Environ** `LINK_BLACK_LIST`

---

**Note:** Regular expressions are supported.

---

`darc.const.LINK_FALLBACK: bool`

Fallback value for `match_host()`.

**Default** `False`

**Environ** `LINK_FALLBACK`

`darc.const.MIME_WHITE_LIST: List[re.Pattern]`

White list of content types should be crawled.

**Default** `[]`

**Environ** `MIME_WHITE_LIST`

---

**Note:** Regular expressions are supported.

---

`darc.const.MIME_BLACK_LIST: List[re.Pattern]`

Black list of content types should be crawled.

**Default** `[]`

**Environ** `MIME_BLACK_LIST`

---

**Note:** Regular expressions are supported.

---

`darc.const.MIME_FALLBACK: bool`

Fallback value for `match_mime()`.

**Default** `False`

**Environ** `MIME_FALLBACK`

`darc.const.PROXY_WHITE_LIST: List[str]`

White list of proxy types should be crawled.

**Default** `[]`

**Environ** `PROXY_WHITE_LIST`

---

**Note:** The proxy types are **case insensitive**.

---

`darc.const.PROXY_BLACK_LIST: List[str]`

Black list of proxy types should be crawled.

**Default** `[]`

**Environ** `PROXY_BLACK_LIST`

---

**Note:** The proxy types are **case insensitive**.

---

`darc.const.PROXY_FALLBACK: bool`

Fallback value for `match_proxy()`.

**Default** `False`  
**Environ** `PROXY_FALLBACK`

## 1.5 Custom Exceptions

The `render_error()` function can be used to render multi-line error messages with `stem.util.term` colours.

The `darc` project provides following custom exceptions:

- `LinkNoReturn`
- `UnsupportedLink`
- `UnsupportedPlatform`
- `UnsupportedProxy`

The `darc` project provides following custom exceptions:

- `TorBootstrapFailed`
- `I2PBootstrapFailed`
- `ZeroNetBootstrapFailed`
- `FreenetBootstrapFailed`
- `APIRequestFailed`
- `SiteNotFoundWarning`
- `LockWarning`
- `TorRenewFailed`
- `RedisCommandFailed`

**exception** `darc.error.APIRequestFailed`

Bases: `Warning`

API submit failed.

**exception** `darc.error.FreenetBootstrapFailed`

Bases: `Warning`

Freenet bootstrap process failed.

**exception** `darc.error.I2PBootstrapFailed`

Bases: `Warning`

I2P bootstrap process failed.

**exception** `darc.error.LinkNoReturn`

Bases: `Exception`

The link has no return value from the hooks.

**exception** `darc.error.LockWarning`

Bases: `Warning`

Failed to acquire Redis lock.

```
exception darc.error.RedisCommandFailed
Bases: Warning
Redis command execution failed.

exception darc.error.SiteNotFoundWarning
Bases: ImportWarning
Site customisation not found.

exception darc.error.TorBootstrapFailed
Bases: Warning
Tor bootstrap process failed.

exception darc.error.TorRenewFailed
Bases: Warning
Tor renew request failed.

exception darc.error.UnsupportedLink
Bases: Exception
The link is not supported.

exception darc.error.UnsupportedPlatform
Bases: Exception
The platform is not supported.

exception darc.error.UnsupportedProxy
Bases: Exception
The proxy is not supported.

exception darc.error.ZeroNetBootstrapFailed
Bases: Warning
ZeroNet bootstrap process failed.
```

`darc.error.render_error(message, colour)`  
Render error message.

The function wraps the `stem.util.term.format()` function to provide multi-line formatting support.

#### Parameters

- `message (str)` – Multi-line message to be rendered with `colour`.
- `colour (stem.util.term.Color)` – Front colour of text, c.f. `stem.util.term.Color`.

**Returns** The rendered error message.

**Return type** `str`

As the websites can be sometimes irritating for their anti-robots verification, login requirements, etc., the `darc` project also provides hooks to customise crawling behaviours around both `requests` and `selenium`.

#### See also:

Such customisation, as called in the `darc` project, site hooks, is site specific, user can set up your own hooks unto a certain site, c.f. `darc.sites` for more information.

Still, since the network is a world full of mysteries and miracles, the speed of crawling will much depend on the response speed of the target website. To boost up, as well as meet the system capacity, the `darc` project introduced multiprocessing, multithreading and the fallback slowest single-threaded solutions when crawling.

---

**Note:** When rendering the target website using selenium powered by the renown Google Chrome, it will require much memory to run. Thus, the three solutions mentioned above would only toggle the behaviour around the use of selenium.

---

To keep the *darc* project as it is a swiss army knife, only the main entrypoint function `darc.process`.  
`process()` is exported in global namespace (and renamed to `darc.darc()`), see below:

---

## CHAPTER TWO

---

## DOCKER INTEGRATION

The `darc` project is integrated with Docker and Compose. Though published to [Docker Hub](#), you can still build by yourself.

---

**Important:** The debug image contains miscellaneous documents, i.e. whole repository in it; and pre-installed some useful tools for debugging, such as IPython, etc.

---

The Docker image is based on [Ubuntu Bionic](#) (18.04 LTS), setting up all Python dependencies for the `darc` project, installing [Google Chrome](#) (version 79.0.3945.36) and corresponding [ChromeDriver](#), as well as installing and configuring [Tor](#), [I2P](#), [ZeroNet](#), [FreeNet](#), [NoIP](#) proxies.

---

**Note:** NoIP is currently not fully integrated in the `darc` due to misunderstanding in the configuration process. Contributions are welcome.

---

When building the image, there is an *optional* argument for setting up a *non-root* user, c.f. environment variable `DARC_USER` and module constant `DARC_USER`. By default, the username is `darc`.

```
FROM ubuntu:bionic

LABEL Name=darc \
      Version=0.6.0

STOPSIGNAL SIGINT
HEALTHCHECK --interval=1h --timeout=1m \
    CMD wget https://httpbin.org/get -O /dev/null || exit 1

ARG DARC_USER="darc"
ENV LANG="C.UTF-8" \
     LC_ALL="C.UTF-8" \
     PYTHONIOENCODING="UTF-8" \
     DEBIAN_FRONTEND="teletype" \
     DARC_USER="${DARC_USER}"
# DEBIAN_FRONTEND="noninteractive"

COPY extra/retry.sh /usr/local/bin/retry
COPY extra/install.py /usr/local/bin/pty-install
COPY vendor/jdk-11.0.7_linux-x64_bin.tar.gz /var/cache/oracle-jdk11-installer-local/

RUN set -x \
    && retry apt-get update \
    && retry apt-get install --yes --no-install-recommends \
```

(continues on next page)

(continued from previous page)

```

    apt-utils \
&& retry apt-get install --yes --no-install-recommends \
    gcc \
    g++ \
    libmagic1 \
    make \
    software-properties-common \
    tar \
    unzip \
    zlib1g-dev \
&& retry add-apt-repository ppa:deadsnakes/ppa --yes \
&& retry add-apt-repository ppa:linuxuprising/java --yes \
&& retry add-apt-repository ppa:i2p-maintainers/i2p --yes
RUN retry apt-get update \
&& retry apt-get install --yes --no-install-recommends \
    python3.8 \
    python3-pip \
    python3-setuptools \
    python3-wheel \
&& ln -sf /usr/bin/python3.8 /usr/local/bin/python3
RUN retry pty-install --stdin '6\n70' apt-get install --yes --no-install-recommends \
    tzdata \
&& retry pty-install --stdin 'yes' apt-get install --yes \
    oracle-javavm-installer-local
RUN retry apt-get install --yes --no-install-recommends \
    sudo \
&& adduser --disabled-password --gecos '' ${DARC_USER} \
&& adduser ${DARC_USER} sudo \
&& echo '%sudo ALL=(ALL) NOPASSWD:ALL' >> /etc/sudoers

## Tor
RUN retry apt-get install --yes --no-install-recommends tor
COPY extra/torrc.bionic /etc/tor/torrc

## I2P
RUN retry apt-get install --yes --no-install-recommends i2p
COPY extra/i2p.bionic /etc/defaults/i2p

## ZeroNet
COPY vendor/ZeroNet-py3-linux64.tar.gz /tmp
RUN set -x \
&& cd /tmp \
&& tar xvpfz ZeroNet-py3-linux64.tar.gz \
&& mv ZeroNet-linux-dist-linux64 /usr/local/src/zeronet
COPY extra/zeronet.bionic.conf /usr/local/src/zeronet/zeronet.conf

## FreeNet
USER darc
COPY vendor/new_installer_offline.jar /tmp
RUN set -x \
&& cd /tmp \
&& ( pty-install --stdin '/home/darc/freenet\n1' java -jar new_installer_offline.jar \
→|| true ) \
&& sudo mv /home/darc/freenet /usr/local/src/freenet
USER root

## NoIP

```

(continues on next page)

(continued from previous page)

```

COPY vendor/noip-duc-linux.tar.gz /tmp
RUN set -x \
  && cd /tmp \
  && tar xvpfz noip-duc-linux.tar.gz \
  && mv noip-2.1.9-1 /usr/local/src/noip \
  && cd /usr/local/src/noip \
  && make
  # && make install

# # set up timezone
# RUN echo 'Asia/Shanghai' > /etc/timezone \
#   && rm -f /etc/localtime \
#   && ln -snf /usr/share/zoneinfo/Asia/Shanghai /etc/localtime \
#   && dpkg-reconfigure -f noninteractive tzdata

COPY vendor/chromedriver_linux64-79.0.3945.36.zip \
  vendor/google-chrome-stable_current_amd64.deb /tmp/
RUN set -x \
  ## ChromeDriver
  && unzip -d /usr/bin /tmp/chromedriver_linux64-79.0.3945.36.zip \
  && which chromedriver \
  ## Google Chrome
  && ( dpkg --install /tmp/google-chrome-stable_current_amd64.deb || true ) \
  && retry apt-get install --fix-broken --yes --no-install-recommends \
  && dpkg --install /tmp/google-chrome-stable_current_amd64.deb \
  && which google-chrome

# Using pip:
COPY requirements.txt /tmp
RUN python3 -m pip install -r /tmp/requirements.txt --no-cache-dir

RUN set -x \
  && rm -rf \
    ## APT repository lists
    /var/lib/apt/lists/* \
    ## Python dependencies
    /tmp/requirements.txt \
    /tmp/pip \
    ## ChromeDriver
    /tmp/chromedriver_linux64-79.0.3945.36.zip \
    ## Google Chrome
    /tmp/google-chrome-stable_current_amd64.deb \
    ## Vendors
    /tmp/new_installer_offline.jar \
    /tmp/noip-duc-linux.tar.gz \
    /tmp/ZeroNet-py3-linux64.tar.gz \
  #&& apt-get remove --auto-remove --yes \
  #      software-properties-common \
  #      unzip \
  && apt-get autoremove -y \
  && apt-get autoclean \
  && apt-get clean

ENTRYPOINT [ "python3", "-m", "darc" ]
#ENTRYPOINT [ "bash", "/app/run.sh" ]
CMD [ "--help" ]

```

(continues on next page)

(continued from previous page)

```
WORKDIR /app
COPY darc/ /app/darc/
COPY LICENSE \
    MANIFEST.in \
    README.rst \
    extra/run.sh \
    setup.cfg \
    setup.py \
    test_darc.py /app/
RUN python3 -m pip install -e .
```

**Note:**

- retry is a shell script for retrying the commands until success

```
#!/usr/bin/env bash

while true; do
    >&2 echo "+ $@"
    $@ && break
    >&2 echo "exit: $?"
done
>&2 echo "exit: 0"
```

- pty-install is a Python script simulating user input for APT package installation with DEBIAN\_FRONTEND set as Teletype.

```
#!/usr/bin/env python3
# -*- coding: utf-8 -*-
"""Install packages requiring interactions."""

import argparse
import os
import subprocess
import sys
import tempfile

def get_parser():
    """Argument parser."""
    parser = argparse.ArgumentParser('install',
                                    description='pseudo-interactive package installer')
    parser.add_argument('-i', '--stdin', help='content for input')
    parser.add_argument('command', nargs=argparse.REMAINDER, help='command to execute')

    return parser

def main():
    """Entrypoint."""
    parser = get_parser()
    args = parser.parse_args()
    text = args.stdin.encode().decode('unicode_escape')
```

(continues on next page)

(continued from previous page)

```

path = tempfile.mktemp(prefix='install-')
with open(path, 'w') as file:
    file.write(text)

with open(path, 'r') as file:
    proc = subprocess.run(args.command, stdin=file)  # pylint: disable=subprocess-
    ↪run-check

os.remove(path)
return proc.returncode

if __name__ == "__main__":
    sys.exit(main())

```

As always, you can also use Docker Compose to manage the `darc` image. Environment variables can be set as described in the [configuration](#) section.

```

version: '3'

services:
  crawler:
    image: jsnbzh/darc:latest
    build: &build
    context: .
    args:
      # non-root user
      DARC_USER: "darc"
    container_name: crawler
    #entrypoint: [ "bash", "/app/run.sh" ]
    command: [ "--type", "crawler",
               "--file", "/app/text/market.txt",
               "--file", "/app/text/top-20k.txt",
               "--file", "/app/text/i2p.txt",
               "--file", "/app/text/zeronet.txt",
               "--file", "/app/text/freenet.txt",
               "--file", "/app/text/ahmia.fi_onions.txt",
               "--file", "/app/text/tor.new.txt" ]
    depends_on: &depends_on
      - db
  environment:
    ## [PYTHON] force the stdout and stderr streams to be unbuffered
    PYTHONUNBUFFERED: 1
    # reboot mode
    DARC_REBOOT: 0
    # debug mode
    DARC_DEBUG: 0
    # verbose mode
    DARC_VERBOSE: 1
    # force mode (ignore robots.txt)
    DARC_FORCE: 1
    # check mode (check proxy and hostname before crawling)
    DARC_CHECK: 1
    # check mode (check content type before crawling)

```

(continues on next page)

(continued from previous page)

```

DARC_CHECK_CONTENT_TYPE: 0
# save mode
DARC_SAVE: 0
# save mode (for requests)
DAVE_SAVE_REQUESTS: 0
# save mode (for selenium)
DAVE_SAVE_SELENIUM: 0
# processes
DARC_CPU: 16
# multiprocessing
DARC_MULTIPROCESSING: 1
# multithreading
DARC_MULTITHREADING: 0
# time lapse
DARC_WAIT: 60
# data storage
PATH_DATA: "data"
# Redis URL
#REDIS_URL: 'redis://r-j6cd2kyxmdmtwsuwwq:zft%4013917331612@r-
˓→j6cd2kyxmdmtwsuwwq.redis.rds.aliyuncs.com'
# database URL
DB_URL: 'mysql://'
˓→root:b8y9dpz3MJSQtwnZIW77ydASBOYfzA7HJfugv77wLrWQzrjCx5m3spoaiqRi4kU52syYy2jxJZR3U2kwPkeVTA@db
˓→'
# max pool
DARC_MAX_POOL: 10
# Tor proxy & control port
TOR_PORT: 9050
TOR_CTRL: 9051
# Tor management method
TOR_STEM: 1
# Tor authentication
TOR_PASS: "16:B9D36206B5374B3F609045F9609EE670F17047D88FF713EFB9157EA39F"
# Tor bootstrap retry
TOR_RETRY: 10
# Tor bootstrap wait
TOR_WAIT: 90
# Tor bootstrap config
TOR_CFG: "{}"
# I2P port
I2P_PORT: 4444
# I2P bootstrap retry
I2P_RETRY: 10
# I2P bootstrap wait
I2P_WAIT: 90
# I2P bootstrap config
I2P_ARGS: ""
# ZeroNet port
ZERONET_PORT: 43110
# ZeroNet bootstrap retry
ZERONET_RETRY: 10
# ZeroNet project path
ZERONET_PATH: "/usr/local/src/zeronet"
# ZeroNet bootstrap wait
ZERONET_WAIT: 90
# ZeroNet bootstrap config
ZERONET_ARGS: ""

```

(continues on next page)

(continued from previous page)

```

# Freenet port
FREENET_PORT: 8888
# Freenet bootstrap retry
FREENET_RETRY: 0
# Freenet project path
FREENET_PATH: "/usr/local/src/freenet"
# Freenet bootstrap wait
FREENET_WAIT: 90
# Freenet bootstrap config
FREENET_ARGS: ""
# time delta for caches in seconds
TIME_CACHE: 2_592_000 # 30 days
# time to wait for selenium
SE_WAIT: 5
# extract link pattern
LINK_WHITE_LIST: '[  

    ".*?\.\.onion",  

    ".*?\.\.i2p", "127\.\.0\.\.0\.\.1:7657", "localhost:7657", "127\.\.0\.\.0\.\.1:7658",  

    ↪ "localhost:7658",  

    "127\.\.0\.\.0\.\.1:43110", "localhost:43110",  

    "127\.\.0\.\.0\.\.1:8888", "localhost:8888"  

]'
# link black list
LINK_BLACK_LIST: '[ "(.*\.\.)?facebookcorewwi\.\.onion", "(.*\.\.)?  

    ↪ nytimes3xbfgragh\.\.onion" ]'
# link fallback flag
LINK_FALLBACK: 1
# content type white list
MIME_WHITE_LIST: '[ "text/html", "application/xhtml+xml" ]'
# content type black list
MIME_BLACK_LIST: '[ "text/css", "application/javascript", "text/json" ]'
# content type fallback flag
MIME_FALLBACK: 0
# proxy type white list
PROXY_WHITE_LIST: '[ "tor", "i2p", "freenet", "zeronet" ]'
# proxy type black list
PROXY_BLACK_LIST: '[ "null", "data" ]'
# proxy type fallback flag
PROXY_FALLBACK: 0
# API retry times
API_RETRY: 10
# API URLs
#API_NEW_HOST: 'https://example.com/api/new_host'
#API_REQUESTS: 'https://example.com/api/requests'
#API_SELENIUM: 'https://example.com/api/selenium'
restart: "always"
networks: &networks
- darc
volumes: &volumes
- ./text:/app/text
- ./extra:/app/extra
- /data/darc:/app/data

loader:
  image: jsnbzh/darc:latest
  build: *build
  container_name: loader

```

(continues on next page)

(continued from previous page)

```

#entrypoint: [ "bash", "/app/run.sh" ]
command: [ "--type", "loader" ]
depends_on: *depends_on
environment:
    ## [PYTHON] force the stdout and stderr streams to be unbuffered
    PYTHONUNBUFFERED: 1
    # reboot mode
    DARC_REBOOT: 0
    # debug mode
    DARC_DEBUG: 0
    # verbose mode
    DARC_VERBOSE: 1
    # force mode (ignore robots.txt)
    DARC_FORCE: 1
    # check mode (check proxy and hostname before crawling)
    DARC_CHECK: 1
    # check mode (check content type before crawling)
    DARC_CHECK_CONTENT_TYPE: 0
    # save mode
    DARC_SAVE: 0
    # save mode (for requests)
    DAVE_SAVE_REQUESTS: 0
    # save mode (for selenium)
    DAVE_SAVE_SELENIUM: 0
    # processes
    DARC_CPU: 1
    # multiprocessing
    DARC_MULTIPROCESSING: 0
    # multithreading
    DARC_MULTITHREADING: 0
    # time lapse
    DARC_WAIT: 60
    # data storage
    PATH_DATA: "data"
    # Redis URL
    #REDIS_URL: 'redis://r-j6cd2kyxmdmtwsuwwq:zft%4013917331612@r-
    ↪j6cd2kyxmdmtwsuwwq.redis.rds.aliyuncs.com'
    # database URL
    DB_URL: 'mysql://
    ↪root:b8y9dpz3MJSQtwnZIW77ydASBOYfzA7HJfugv77wLrWQzrjCx5m3spoaiqRi4kU52syYy2jxJZR3U2kwP
    ↪kEVTA@db
    ↪'
    # max pool
    DARC_MAX_POOL: 10
    # Tor proxy & control port
    TOR_PORT: 9050
    TOR_CTRL: 9051
    # Tor management method
    TOR_STEM: 1
    # Tor authentication
    TOR_PASS: "16:B9D36206B5374B3F609045F9609EE670F17047D88FF713EFB9157EA39F"
    # Tor bootstrap retry
    TOR_RETRY: 10
    # Tor bootstrap wait
    TOR_WAIT: 90
    # Tor bootstrap config
    TOR_CFG: "{}"
    # I2P port

```

(continues on next page)

(continued from previous page)

```

I2P_PORT: 4444
# I2P bootstrap retry
I2P_RETRY: 10
# I2P bootstrap wait
I2P_WAIT: 90
# I2P bootstrap config
I2P_ARGS: ""
# ZeroNet port
ZERONET_PORT: 43110
# ZeroNet bootstrap retry
ZERONET_RETRY: 10
# ZeroNet project path
ZERONET_PATH: "/usr/local/src/zeronet"
# ZeroNet bootstrap wait
ZERONET_WAIT: 90
# ZeroNet bootstrap config
ZERONET_ARGS: ""
# Freenet port
FREENET_PORT: 8888
# Freenet bootstrap retry
FREENET_RETRY: 0
# Freenet project path
FREENET_PATH: "/usr/local/src/freenet"
# Freenet bootstrap wait
FREENET_WAIT: 90
# Freenet bootstrap config
FREENET_ARGS: ""
# time delta for caches in seconds
TIME_CACHE: 2_592_000 # 30 days
# time to wait for selenium
SE_WAIT: 5
# extract link pattern
LINK_WHITE_LIST: '['
    ".*?\.\.onion",
    ".*?\.\.i2p", "127\\\.0\\\.0\\\.1:7657", "localhost:7657", "127\\\.0\\\.0\\\.1:7658",
    ↪ "localhost:7658",
    "127\\\.0\\\.0\\\.1:43110", "localhost:43110",
    "127\\\.0\\\.0\\\.1:8888", "localhost:8888"
]
# link black list
LINK_BLACK_LIST: '[ "(.*\\\.)?facebookcorewwwi\\\.onion", "(.*\\\.)?nytimes3xbfgragh\\\.onion" ]'
# link fallback flag
LINK_FALLBACK: 1
# content type white list
MIME_WHITE_LIST: '[ "text/html", "application/xhtml+xml" ]'
# content type black list
MIME_BLACK_LIST: '[ "text/css", "application/javascript", "text/json" ]'
# content type fallback flag
MIME_FALLBACK: 0
# proxy type white list
PROXY_WHITE_LIST: '[ "tor", "i2p", "freenet", "zeronet" ]'
# proxy type black list
PROXY_BLACK_LIST: '[ "null", "data" ]'
# proxy type fallback flag
PROXY_FALLBACK: 0
# API retry times

```

(continues on next page)

(continued from previous page)

```

API_RETRY: 10
# API URLs
#API_NEW_HOST: 'https://example.com/api/new_host'
#API_REQUESTS: 'https://example.com/api/requests'
#API_SELENIUM: 'https://example.com/api/selenium'
restart: "always"
networks: *networks
volumes: *volumes

db:
  image: mysql
  container_name: db
  command: --default-authentication-plugin=mysql_native_password
  expose:
    - 3306
  restart: "always"
  environment:
    MYSQL_ROOT_PASSWORD:
↳ "b8y9dpz3MJSQtwnZIW77ydASBOYfzA7HJfugv77wLrWQzrjCx5m3spoaiqRi4kU52syYy2jxJZR3U2kwPkEVTA
↳ "
    MYSQL_DATABASE: "darc"
  networks: *networks
  volumes:
    - /data/darc/mysql:/var/lib/mysql

# network settings
networks:
  darc:
    driver: bridge

```

**Note:** Should you wish to run *darc* in reboot mode, i.e. set *DARC\_REBOOT* and/or *REBOOT* as *True*, you may wish to change the entrypoint to

```
bash /app/run.sh
```

where *run.sh* is a shell script wraps around *darc* especially for reboot mode.

```

#!/usr/bin/env bash

set -e

# time lapse
WAIT=${DARC_WAIT=10}

# signal handlers
trap '[ -f ${PATH_DATA}/darc.pid ] && kill -2 $(cat ${PATH_DATA}/darc.pid)' SIGINT
↳ SIGTERM SIGKILL

# initialise
echo "+ Starting application..."
python3 -m darc $@
sleep ${WAIT}

# mainloop
while true; do

```

(continues on next page)

(continued from previous page)

```
echo "+ Restarting application..."  
python3 -m darc  
sleep ${WAIT}  
done
```

---

In such scenario, you can customise your `run.sh` to, for instance, archive then upload current data crawled by `darc` to somewhere else and save up some disk space.

---



## WEB BACKEND DEMO

This is a demo of API for communication between the `darc` crawlers (`darc.submit`) and web UI.

Assuming the web UI is developed using the `Flask` microframework.

```
# -*- coding: utf-8 -*-

import sys

import flask # pylint: disable=import-error

# Flask application
app = flask.Flask(__file__)

@app.route('/api/new_host', methods=['POST'])
def new_host():
    """When a new host is discovered, the :mod:`darc` crawler will submit the
    host information. Such includes ``robots.txt`` (if exists) and
    ``sitemap.xml`` (if any).

    Data format::

        {
            // partial flag - true / false
            "$PARTIAL$": ...,
            // metadata of URL
            "[metadata)": {
                // original URL - <scheme>://<netloc>/<path>;<params>?<query>#
            },
            "url": ...,
            // proxy type - null / tor / i2p / zeronet / freenet
            "proxy": ...,
            // hostname / netloc, c.f. ``urllib.parse.urlparse``
            "host": ...,
            // base folder, relative path (to data root path ``PATH_DATA``) in_
            "base": ...,
            // sha256 of URL as name for saved files (timestamp is in ISO format)
            // JSON log as this one - <base>/<name>_<timestamp>.json
            // HTML from requests - <base>/<name>_<timestamp>_raw.html
            // HTML from selenium - <base>/<name>_<timestamp>.html
            // generic data files - <base>/<name>_<timestamp>.dat
            "name": ...
        },
    """

    return jsonify({
        "status": "ok"
    })
}
```

(continues on next page)

(continued from previous page)

```

// requested timestamp in ISO format as in name of saved file
"Timestamp": ...,
// original URL
"URL": ...,
// robots.txt from the host (if not exists, then ``null``)
"Robots": {
    // path of the file, relative path (to data root path ``PATH_DATA``)
    ↵in container
        // - <proxy>/<scheme>/<host>/robots.txt
        "path": ...,
        // content of the file (**base64** encoded)
        "data": ...,
    },
    // sitemaps from the host (if none, then ``null``)
    "Sitemaps": [
        {
            // path of the file, relative path (to data root path ``PATH_
            ↵DATA``) in container
                // - <proxy>/<scheme>/<host>/sitemap_<name>.txt
                "path": ...,
                // content of the file (**base64** encoded)
                "data": ...,
            },
            ...
        ],
        // hosts.txt from the host (if proxy type is ``i2p``; if not exists, then
        ↵``null``)
        "Hosts": {
            // path of the file, relative path (to data root path ``PATH_DATA``)
            ↵in container
                // - <proxy>/<scheme>/<host>/hosts.txt
                "path": ...,
                // content of the file (**base64** encoded)
                "data": ...,
            }
        }
    }

"""
# JSON data from the request
data = flask.request.json # pylint: disable=unused-variable

# do whatever processing needed
...

@app.route('/api/requests', methods=['POST'])
def from_requests():
    """When crawling, we'll first fetch the URL using ``requests``, to check
    its availability and to save its HTTP headers information. Such information
    will be submitted to the web UI.

    Data format::

        {
            // metadata of URL
            "[metadata)": {
                // original URL - <scheme>://<netloc>/<path>;<params>?<query>#
    ↵<fragment>

```

(continues on next page)

(continued from previous page)

```

"url": ....
// proxy type - null / tor / i2p / zeronet / freenet
"proxy": ....
// hostname / netloc, c.f. ``urllib.parse.urlparse``
"host": ....
// base folder, relative path (to data root path ``PATH_DATA``) in_
↪container - <proxy>/<scheme>/<host>
"base": ....
// sha256 of URL as name for saved files (timestamp is in ISO format)
// JSON log as this one - <base>/<name>_<timestamp>.json
// HTML from requests - <base>/<name>_<timestamp>_raw.html
// HTML from selenium - <base>/<name>_<timestamp>.html
// generic data files - <base>/<name>_<timestamp>.dat
"name": ...

},
// requested timestamp in ISO format as in name of saved file
"Timestamp": ....
// original URL
"URL": ....
// request method
"Method": "GET",
// response status code
>Status-Code": ....
// response reason
"Reason": ....
// response cookies (if any)
"Cookies": {
    ...
},
// session cookies (if any)
"Session": {
    ...
},
// request headers (if any)
"Request": {
    ...
},
// response headers (if any)
"Response": {
    ...
},
// Content type
"Content-Type": ....
// requested file (if not exists, then ``null``)
"Document": {
    // path of the file, relative path (to data root path ``PATH_DATA``)_in container
    // - <proxy>/<scheme>/<host>/<name>_<timestamp>_raw.html
    // or if the document is of generic content type, i.e. not HTML
    // - <proxy>/<scheme>/<host>/<name>_<timestamp>.dat
    "path": ....
    // content of the file (**base64** encoded)
    "data": ....
},
// redirection history (if any)
"History": [
    // same records as the original response

```

(continues on next page)

(continued from previous page)

```

        {"...": "..."}
    }
}

"""
# JSON data from the request
data = flask.request.json # pylint: disable=unused-variable

# do whatever processing needed
...

@app.route('/api/selenium', methods=['POST'])
def from_selenium():
    """After crawling with ``requests``, we'll then render the URL using
    ``selenium`` with Google Chrome and its driver, to provide a fully rendered
    web page. Such information will be submitted to the web UI.

    Note:
        This information is optional, only provided if the content type from
        ``requests`` is HTML, status code < 400, and HTML data not empty.

    Data format::

    {
        // metadata of URL
        "[metadata)": {
            // original URL - <scheme>://<netloc>/<path>;<params>?<query>#
        ↪<fragment>
            "url": ...,
            // proxy type - null / tor / i2p / zeronet / freenet
            "proxy": ...,
            // hostname / netloc, c.f. ``urllib.parse.urlparse``
            "host": ...,
            // base folder, relative path (to data root path ``PATH_DATA``) in
        ↪containter - <proxy>/<scheme>/<host>
            "base": ...,
            // sha256 of URL as name for saved files (timestamp is in ISO format)
            // JSON log as this one - <base>/<name>_<timestamp>.json
            // HTML from requests - <base>/<name>_<timestamp>_raw.html
            // HTML from selenium - <base>/<name>_<timestamp>.html
            // generic data files - <base>/<name>_<timestamp>.dat
            "name": ...
        },
        // requested timestamp in ISO format as in name of saved file
        "Timestamp": ...,
        // original URL
        "URL": ...,
        // rendered HTML document (if not exists, then ``null``)
        "Document": {
            // path of the file, relative path (to data root path ``PATH_DATA``) in
        ↪in container
            // - <proxy>/<scheme>/<host>/<name>_<timestamp>.html
            "path": ...,
            // content of the file (**base64** encoded)
            "data": ...
        },
    }
}

```

(continues on next page)

(continued from previous page)

```
// web page screenshot (if not exists, then ``null``)
"Screenshot": {
    // path of the file, relative path (to data root path ``PATH_DATA``)
→in container
    // - <proxy>/<scheme>/<host>/<name>_<timestamp>.png
    "path": ...,
    // content of the file (**base64** encoded)
    "data": ...,
}
}

"""
# JSON data from the request
data = flask.request.json # pylint: disable=unused-variable

# do whatever processing needed
...

if __name__ == "__main__":
    sys.exit(app.run())
```



---

CHAPTER  
FOUR

---

## DATA MODELS DEMO

This is a demo of data models for database storage of the submitted data from the `darc` crawlers.

Assuming the database is using `peewee` as ORM and `MySQL` as backend.

```
# -*- coding: utf-8 -*-

import datetime
import os

import peewee
import playhouse.shortcuts

# database client
DB = playhouse.db_url.connect(os.getenv('DB_URL', 'mysql://127.0.0.1'))

def table_function(model_class: peewee.Model) -> str:
    """Generate table name dynamically.

    The function strips ``Model`` from the class name and
    calls :func:`peewee.make_snake_case` to generate a
    proper table name.

    Args:
        model_class: Data model class.

    Returns:
        Generated table name.

    """
    name: str = model_class.__name__
    if name.endswith('Model'):
        name = name[:-5] # strip ``Model`` suffix
    return peewee.make_snake_case(name)

class BaseMeta:
    """Basic metadata for data models."""

    #: Reference database storage (c.f. :class:`~darc.const.DB`).
    database = DB

    #: Generate table name dynamically (c.f. :func:`~darc.model.table_function`).
    table_function = table_function
```

(continues on next page)

(continued from previous page)

```

class BaseModel(peewee.Model):
    """Base model with standard patterns.

    Notes:
        The model will implicitly have a :class:`~peewee.AutoField` attribute named as :attr:`id`.

    """

    #: Basic metadata for data models.
    Meta = BaseMeta

    def to_dict(self, keep_id: bool = False):
        """Convert record to :obj:`dict`.

        Args:
            keep_id: If keep the ID auto field.

        Returns:
            The data converted through :func:`playhouse.shortcuts.model_to_dict`.

        """
        data = playhouse.shortcuts.model_to_dict(self)
        if keep_id:
            return data

        if 'id' in data:
            del data['id']
        return data

class HostnameModel(BaseModel):
    """Data model for a hostname record."""

    #: Hostname (c.f. :attr:`link.host <darc.link.Link.host>`).
    hostname: str = peewee.TextField()
    #: Proxy type (c.f. :attr:`link.proxy <darc.link.Link.proxy>`).
    proxy: str = peewee.CharField(max_length=8)

    #: Timestamp of first ``new_host`` submission.
    discovery: datetime.datetime = peewee.DateTimeField()
    #: Timestamp of last related submission.
    last_seen: datetime.datetime = peewee.DateTimeField()

class RobotsModel(BaseModel):
    """Data model for ``robots.txt`` data."""

    #: Hostname (c.f. :attr:`link.host <darc.link.Link.host>`).
    host: HostnameModel = peewee.ForeignKeyField(HostnameModel, backref='robots')
    #: Timestamp of the submission.
    timestamp: datetime.datetime = peewee.DateTimeField()

    #: Document data as :obj:`bytes`.
    data: bytes = peewee.BlobField()

```

(continues on next page)

(continued from previous page)

```

#: Path to the document.
path: str = peewee.CharField()

class SitemapModel(BaseModel):
    """Data model for ``sitemap.xml`` data."""

    #: Hostname (c.f. :attr:`link.host <darc.link.Link.host>`).
    host: HostnameModel = peewee.ForeignKeyField(HostnameModel, backref='sitemaps')
    #: Timestamp of the submission.
    timestamp: datetime.datetime = peewee.DateTimeField()

    #: Document data as :obj:`bytes`.
    data: bytes = peewee.BlobField()
    #: Path to the document.
    path: str = peewee.CharField()

class HostsModel(BaseModel):
    """Data model for ``hosts.txt`` data."""

    #: Hostname (c.f. :attr:`link.host <darc.link.Link.host>`).
    host: HostnameModel = peewee.ForeignKeyField(HostnameModel, backref='hosts')
    #: Timestamp of the submission.
    timestamp: datetime.datetime = peewee.DateTimeField()

    #: Document data as :obj:`bytes`.
    data: bytes = peewee.BlobField()
    #: Path to the document.
    path: str = peewee.CharField()

class URLModel(BaseModel):
    """Data model for a requested URL."""

    #: Timestamp of last related submission.
    last_seen: datetime.datetime = peewee.DateTimeField()
    #: Original URL (c.f. :attr:`link.url <darc.link.Link.url>`).
    url: str = peewee.TextField()

    #: Hostname (c.f. :attr:`link.host <darc.link.Link.host>`).
    host: HostnameModel = peewee.ForeignKeyField(HostnameModel, backref='urls')
    #: Proxy type (c.f. :attr:`link.proxy <darc.link.Link.proxy>`).
    proxy: str = peewee.CharField(max_length=8)

    #: Base path (c.f. :attr:`link.base <darc.link.Link.base>`).
    base: str = peewee.CharField()
    #: Link hash (c.f. :attr:`link.name <darc.link.Link.name>`).
    name: str = peewee.FixedCharField(max_length=64)

class RequestsDocumentModel(BaseModel):
    """Data model for documents from ``requests`` submission."""

    #: Original URL (c.f. :attr:`link.url <darc.link.Link.url>`).
    url: URLModel = peewee.ForeignKeyField(URLModel, backref='requests')

```

(continues on next page)

(continued from previous page)

```
#: Document data as :obj:`bytes`.  
data: bytes = peewee.BlobField()  
#: Path to the document.  
path: str = peewee.CharField()  
  
class SeleniumDocumentModel(BaseModel):  
    """Data model for documents from ``selenium`` submission."  
  
    #: Original URL (c.f. :attr:`link.url <darc.link.Link.url>`).  
    url: URLModel = peewee.ForeignKeyField(URLModel, backref='selenium')  
  
    #: Document data as :obj:`bytes`.  
    data: bytes = peewee.BlobField()  
    #: Path to the document.  
    path: str = peewee.CharField()
```

## AUXILIARY SCRIPTS

Since the `darc` project can be deployed through *Docker Integration*, we provided some auxiliary scripts to help with the deployment.

### 5.1 Health Check

#### File location

- Entry point: `extra/healthcheck.py`
- System V service: `extra/healthcheck.service`

```
usage: healthcheck [-h] [-f FILE] [-i INTERVAL] ...

health check running container

positional arguments:
  services           name of services

optional arguments:
  -h, --help          show this help message and exit
  -f FILE, --file FILE path to compose file
  -i INTERVAL, --interval INTERVAL
                      interval (in seconds) of health check
```

This script will watch the running status of containers managed by Docker Compose. If the containers are stopped or of *unhealthy* status, it will bring the containers back alive.

Also, as the internal program may halt unexpectedly whilst the container remains *healthy*, the script will watch if the program is still active through its output messages. If inactive, the script will restart the containers.

### 5.2 Upload API Submission Files

#### File location

- Entry point: `extra/upload.py`
- Helper script: `extra/upload.sh`
- System V service: `extra/upload.service`

```
usage: upload [-h] [-f FILE] [-p PATH] [-i INTERVAL] -H HOST [-U USER]

upload API submission files

optional arguments:
  -h, --help            show this help message and exit
  -f FILE, --file FILE path to compose file
  -p PATH, --path PATH  path to data storage
  -i INTERVAL, --interval INTERVAL
                        interval (in seconds) to upload
  -H HOST, --host HOST  upstream hostname
  -U USER, --user USER  upstream user credential
```

This script will automatically upload API submission files, c.f. `darc.submit`, using `curl(1)`. The `--user` option is supplied for the same option of `curl(1)`.

When uploading, the script will *pause* the running containers and it will *unpause* them upon completion.

## 5.3 Remove Repeated Lines

**File location** `extra/uniq.py`

This script works the same as `uniq(1)`, except it filters one input line at a time without putting pressure onto memory utilisation.

`darc` is designed as a swiss army knife for darkweb crawling. It integrates `requests` to collect HTTP request and response information, such as cookies, header fields, etc. It also bundles `selenium` to provide a fully rendered web page and screenshot of such view.

There are two types of *workers*:

- `crawler` – runs the `darc.crawl.crawler()` to provide a fresh view of a link and test its connectability
- `loader` – run the `darc.crawl.loader()` to provide an in-depth view of a link and provide more visual information

The general process can be described as following for *workers* of `crawler` type:

1. `process_crawler()`: obtain URLs from the `requests` link database (c.f. `load_requests()`), and feed such URLs to `crawler()`.

---

**Note:** If `FLAG_MP` is `True`, the function will be called with *multiprocessing* support; if `FLAG_TH` if `True`, the function will be called with *multithreading* support; if none, the function will be called in single-threading.

2. `crawler()`: parse the URL using `parse_link()`, and check if need to crawl the URL (c.f. `PROXY_WHITE_LIST`, `PROXY_BLACK_LIST`, `LINK_WHITE_LIST` and `LINK_BLACK_LIST`); if true, then crawl the URL with `requests`.

If the URL is from a brand new host, `darc` will first try to fetch and save `robots.txt` and sitemaps of the host (c.f. `save_robots()` and `save_sitemap()`), and extract then save the links from sitemaps (c.f. `read_sitemap()`) into link database for future crawling (c.f. `save_requests()`). Also, if the submission API is provided, `submit_new_host()` will be called and submit the documents just fetched.

If `robots.txt` presented, and `FORCE` is `False`, `darc` will check if allowed to crawl the URL.

---

**Note:** The root path (e.g. / in <https://www.example.com/>) will always be crawled ignoring robots.txt.

---

At this point, `darc` will call the customised hook function from `darc.sites` to crawl and get the final response object. `darc` will save the session cookies and header information, using `save_headers()`.

---

**Note:** If `requests.exceptions.InvalidSchema` is raised, the link will be saved by `save_invalid()`. Further processing is dropped.

---

If the content type of response document is not ignored (c.f. `MIME_WHITE_LIST` and `MIME_BLACK_LIST`), `submit_requests()` will be called and submit the document just fetched.

If the response document is HTML (`text/html` and `application/xhtml+xml`), `extract_links()` will be called then to extract all possible links from the HTML document and save such links into the database (c.f. `save_requests()`).

And if the response status code is between 400 and 600, the URL will be saved back to the link database (c.f. `save_requests()`). If NOT, the URL will be saved into selenium link database to proceed next steps (c.f. `save_selenium()`).

The general process can be described as following for `workers` of `loader` type:

1. `process_loader()`: in the meanwhile, `darc` will obtain URLs from the selenium link database (c.f. `load_selenium()`), and feed such URLs to `loader()`.

---

**Note:** If `FLAG_MP` is `True`, the function will be called with *multiprocessing* support; if `FLAG_TH` if `True`, the function will be called with *multithreading* support; if none, the function will be called in single-threading.

---

2. `loader()`: parse the URL using `parse_link()` and start loading the URL using selenium with Google Chrome.

At this point, `darc` will call the customised hook function from `darc.sites` to load and return the original WebDriver object.

If successful, the rendered source HTML document will be saved, and a full-page screenshot will be taken and saved.

If the submission API is provided, `submit_selenium()` will be called and submit the document just loaded.

Later, `extract_links()` will be called then to extract all possible links from the HTML document and save such links into the `requests` database (c.f. `save_requests()`).



---

CHAPTER  
SIX

---

## INSTALLATION

---

**Note:** *darc* supports Python all versions above and includes **3.6**. Currently, it only supports and is tested on Linux (*Ubuntu 18.04*) and macOS (*Catalina*).

When installing in Python versions below **3.8**, *darc* will use *walrus* to compile itself for backport compatibility.

---

```
pip install darc
```

Please make sure you have Google Chrome and corresponding version of Chrome Driver installed on your system.

---

**Important:** Starting from version **0.3.0**, we introduced *Redis* for the task queue database backend.

Since version **0.6.0**, we introduced relationship database storage (e.g. *MySQL*, *SQLite*, *PostgreSQL*, etc.) for the task queue database backend, besides the *Redis* database, since it can be too much memory-costly when the task queue becomes vary large.

Please make sure you have one of the backend database installed, configured, and running when using the *darc* project.

---

However, the *darc* project is shipped with Docker and Compose support. Please see *Docker Integration* for more information.

Or, you may refer to and/or install from the *Docker Hub* repository:

```
docker pull jsnbzh/darc[:TAGNAME]
```



---

CHAPTER  
SEVEN

---

## USAGE

The *darc* project provides a simple CLI:

```
usage: darc [-h] [-f FILE] ...

the darkweb crawling swiss army knife

positional arguments:
  link           links to craw

optional arguments:
  -h, --help      show this help message and exit
  -f FILE, --file FILE  read links from file
```

It can also be called through module entrypoint:

```
python -m python-darc ...
```

---

**Note:** The link files can contain **comment** lines, which should start with `#`. Empty lines and comment lines will be ignored when loading.

---



## CONFIGURATION

Though simple CLI, the `darc` project is more configurable by environment variables.

### 8.1 General Configurations

#### DARC\_REBOOT

**Type** `bool(int)`

**Default** 0

If exit the program after first round, i.e. crawled all links from the `requests` link database and loaded all links from the `selenium` link database.

This can be useful especially when the capacity is limited and you wish to save some space before continuing next round. See [Docker integration](#) for more information.

#### DARC\_DEBUG

**Type** `bool(int)`

**Default** 0

If run the program in debugging mode.

#### DARC\_VERBOSE

**Type** `bool(int)`

**Default** 0

If run the program in verbose mode. If DARC\_DEBUG is `True`, then the verbose mode will be always enabled.

#### DARC\_FORCE

**Type** `bool(int)`

**Default** 0

If ignore `robots.txt` rules when crawling (c.f. `crawler()`).

#### DARC\_CHECK

**Type** `bool(int)`

**Default** 0

If check proxy and hostname before crawling (when calling `extract_links()`, `read_sitemap()` and `read_hosts()`).

If DARC\_CHECK\_CONTENT\_TYPE is `True`, then this environment variable will be always set as `True`.

**DARC\_CHECK\_CONTENT\_TYPE**

**Type** `bool(int)`

**Default** 0

If check content type through HEAD requests before crawling (when calling `extract_links()`, `read_sitemap()` and `read_hosts()`).

**DARC\_CPU**

**Type** `int`

**Default** `None`

Number of concurrent processes. If not provided, then the number of system CPUs will be used.

**DARC\_MULTIPROCESSING**

**Type** `bool(int)`

**Default** 1

If enable *multiprocessing* support.

**DARC\_MULTITHREADING**

**Type** `bool(int)`

**Default** 0

If enable *multithreading* support.

---

**Note:** DARC\_MULTIPROCESSING and DARC\_MULTITHREADING can **NOT** be toggled at the same time.

---

**DARC\_USER**

**Type** `str`

**Default** current login user (c.f. `getpass.getuser()`)

*Non-root* user for proxies.

## 8.2 Data Storage

**See also:**

See `darc.save` for more information about source saving.

See `darc.db` for more information about database integration.

**PATH\_DATA**

**Type** `str(path)`

**Default** `data`

Path to data storage.

**REDIS\_URL**

**Type** `str(url)`

**Default** `redis://127.0.0.1`

URL to the Redis database.

#### DB\_URL

**Type** `str(url)`

URL to the RDS storage.

---

**Important:** The task queues will be saved to `darc` database; the data submittsion will be saved to `darcweb` database.

Thus, when providing this environment variable, please do **NOT** specify the database name.

---

#### DARC\_BULK\_SIZE

**Type** `int`

**Default** 100

*Bulk* size for updating databases.

**See also:**

- `darc.db.save_requests()`
- `darc.db.save_selenium()`

#### LOCK\_TIMEOUT

**Type** `float`

**Default** 10

Lock blocking timeout.

---

**Note:** If is an infinit `inf`, no timeout will be applied.

---

**See also:**

Get a lock from `darc.db.get_lock()`.

#### DARC\_MAX\_POOL

**Type** `int`

**Default** 1\_000

Maximum number of links loaded from the database.

---

**Note:** If is an infinit `inf`, no limit will be applied.

---

**See also:**

- `darc.db.load_requests()`
- `darc.db.load_selenium()`

#### REDIS\_LOCK

**Type** `bool(int)`

**Default** 0

If use Redis (Lua) lock to ensure process/thread-safely operations.

**See also:**

Toggles the behaviour of `darc.db.get_lock()`.

#### **REDIS\_RETRY**

**Type** int

**Default** 10

Retry interval between each Redis command failure.

---

**Note:** If is an infinit `inf`, no interval will be applied.

---

**See also:**

Toggles the behaviour of `darc.db.redis_command()`.

## 8.3 Web Crawlers

#### **DARC\_WAIT**

**Type** float

**Default** 60

Time interval between each round when the `requests` and/or `selenium` database are empty.

#### **DARC\_SAVE**

**Type** bool(int)

**Default** 0

If save processed link back to database.

---

**Note:** If `DARC_SAVE` is `True`, then `DARC_SAVE_REQUESTS` and `DARC_SAVE_SELENIUM` will be forced to be `True`.

---

**See also:**

See `darc.db` for more information about link database.

#### **DARC\_SAVE\_REQUESTS**

**Type** bool(int)

**Default** 0

If save `crawler()` crawled link back to `requests` database.

**See also:**

See `darc.db` for more information about link database.

#### **DARC\_SAVE\_SELENIUM**

**Type** bool(int)

**Default** 0

If save loader () crawled link back to selenium database.

**See also:**

See `darc.db` for more information about link database.

**TIME\_CACHE****Type** float**Default** 60

Time delta for caches in seconds.

The `darc` project supports *caching* for fetched files. `TIME_CACHE` will specify for how long the fetched files will be cached and **NOT** fetched again.

---

**Note:** If `TIME_CACHE` is `None` then caching will be marked as *forever*.

---

**SE\_WAIT****Type** float**Default** 60

Time to wait for selenium to finish loading pages.

---

**Note:** Internally, selenium will wait for the browser to finish loading the pages before return (i.e. the web API event `DOMContentLoaded`). However, some extra scripts may take more time running after the event.

---

## 8.4 White / Black Lists

**LINK\_WHITE\_LIST****Type** List[str] (JSON)**Default** []

White list of hostnames should be crawled.

---

**Note:** Regular expressions are supported.

---

**LINK\_BLACK\_LIST****Type** List[str] (JSON)**Default** []

Black list of hostnames should be crawled.

---

**Note:** Regular expressions are supported.

---

**LINK\_FALLBACK****Type** bool (int)

**Default** 0

Fallback value for `match_host()`.

**MIME\_WHITE\_LIST**

**Type** `List[str]` (JSON)

**Default** []

White list of content types should be crawled.

---

**Note:** Regular expressions are supported.

---

**MIME\_BLACK\_LIST**

**Type** `List[str]` (JSON)

**Default** []

Black list of content types should be crawled.

---

**Note:** Regular expressions are supported.

---

**MIME\_FALLBACK**

**Type** `bool(int)`

**Default** 0

Fallback value for `match_mime()`.

**PROXY\_WHITE\_LIST**

**Type** `List[str]` (JSON)

**Default** []

White list of proxy types should be crawled.

---

**Note:** The proxy types are **case insensitive**.

---

**PROXY\_BLACK\_LIST**

**Type** `List[str]` (JSON)

**Default** []

Black list of proxy types should be crawled.

---

**Note:** The proxy types are **case insensitive**.

---

**PROXY\_FALLBACK**

**Type** `bool(int)`

**Default** 0

Fallback value for `match_proxy()`.

---

**Note:** If provided, LINK\_WHITE\_LIST, LINK\_BLACK\_LIST, MIME\_WHITE\_LIST, MIME\_BLACK\_LIST, PROXY\_WHITE\_LIST and PROXY\_BLACK\_LIST should all be JSON encoded strings.

---

## 8.5 Data Submission

### **SAVE\_DB**

**Type** `bool`

**Default** `True`

Save submitted data to database.

### **API\_RETRY**

**Type** `int`

**Default** `3`

Retry times for API submission when failure.

### **API\_NEW\_HOST**

**Type** `str`

**Default** `None`

API URL for `submit_new_host()`.

### **API\_REQUESTS**

**Type** `str`

**Default** `None`

API URL for `submit_requests()`.

### **API\_SELENIUM**

**Type** `str`

**Default** `None`

API URL for `submit.selenium()`.

---

**Note:** If `API_NEW_HOST`, `API_REQUESTS` and `API_SELENIUM` is `None`, the corresponding submit function will save the JSON data in the path specified by `PATH_DATA`.

---

## 8.6 Tor Proxy Configuration

### DARC\_TOR

**Type** `bool(int)`

**Default** 1

If manage the Tor proxy through `darc`.

### TOR\_PORT

**Type** `int`

**Default** 9050

Port for Tor proxy connection.

### TOR\_CTRL

**Type** `int`

**Default** 9051

Port for Tor controller connection.

### TOR\_PASS

**Type** `str`

**Default** `None`

Tor controller authentication token.

---

**Note:** If not provided, it will be requested at runtime.

---

### TOR\_RETRY

**Type** `int`

**Default** 3

Retry times for Tor bootstrap when failure.

### TOR\_WAIT

**Type** `float`

**Default** 90

Time after which the attempt to start Tor is aborted.

---

**Note:** If not provided, there will be **NO** timeouts.

---

### TOR\_CFG

**Type** `Dict[str, Any]` (JSON)

**Default** `{}`

Tor bootstrap configuration for `stem.process.launch_tor_with_config()`.

---

**Note:** If provided, it should be a JSON encoded string.

---

## 8.7 I2P Proxy Configuration

### DARC\_I2P

**Type** `bool(int)`

**Default** 1

If manage the I2P proxy through `darc`.

### I2P\_PORT

**Type** `int`

**Default** 4444

Port for I2P proxy connection.

### I2P\_RETRY

**Type** `int`

**Default** 3

Retry times for I2P bootstrap when failure.

### I2P\_WAIT

**Type** `float`

**Default** 90

Time after which the attempt to start I2P is aborted.

---

**Note:** If not provided, there will be **NO** timeouts.

---

### I2P\_ARGS

**Type** `str(Shell)`

**Default** ''

I2P bootstrap arguments for `i2prouter start`.

If provided, it should be parsed as command line arguments (c.f. `shlex.split()`).

---

**Note:** The command will be run as DARC\_USER, if current user (c.f. `getpass.getuser()`) is *root*.

---

## 8.8 ZeroNet Proxy Configuration

### DARC\_ZERONET

**Type** `bool(int)`

**Default** 1

If manage the ZeroNet proxy through `darc`.

### ZERONET\_PORT

**Type** `int`

**Default** 4444

Port for ZeroNet proxy connection.

### ZERONET\_RETRY

**Type** `int`

**Default** 3

Retry times for ZeroNet bootstrap when failure.

### ZERONET\_WAIT

**Type** `float`

**Default** 90

Time after which the attempt to start ZeroNet is aborted.

---

**Note:** If not provided, there will be **NO** timeouts.

---

### ZERONET\_PATH

**Type** `str(path)`

**Default** /usr/local/src/zeronet

Path to the ZeroNet project.

### ZERONET\_ARGS

**Type** `str(Shell)`

**Default** ''

ZeroNet bootstrap arguments for `ZeroNet.sh main`.

---

**Note:** If provided, it should be parsed as command line arguments (c.f. `shlex.split()`).

---

## 8.9 Freenet Proxy Configuration

### DARC\_FREENET

**Type** `bool(int)`

**Default** 1

If manage the Freenet proxy through `darc`.

### FREENET\_PORT

**Type** `int`

**Default** 8888

Port for Freenet proxy connection.

### FREENET\_RETRY

**Type** `int`

**Default** 3

Retry times for Freenet bootstrap when failure.

### FREENET\_WAIT

**Type** `float`

**Default** 90

Time after which the attempt to start Freenet is aborted.

**Note:** If not provided, there will be **NO** timeouts.

### FREENET\_PATH

**Type** `str(path)`

**Default** `/usr/local/src/freenet`

Path to the Freenet project.

### FREENET\_ARGS

**Type** `str(Shell)`

**Default** ''

Freenet bootstrap arguments for `run.sh start`.

If provided, it should be parsed as command line arguments (c.f. `shlex.split()`).

**Note:** The command will be run as DARC\_USER, if current user (c.f. `getpass.getuser()`) is `root`.



---

**CHAPTER  
NINE**

---

**INDICES AND TABLES**

- genindex
- modindex
- search



## PYTHON MODULE INDEX

### d

`darc`, 1  
`darc.error`, 20  
`darc.link`, 1  
`darc.proxy`, 6  
`darc.sites`, 13



# INDEX

## Symbols

`__hash__()` (*darc.link.Link method*), 1

### A

`API_NEW_HOST`, 6

`API_REQUESTS`, 6

`API_RETRY`, 6

`API_SELENIUM`, 6

`APIRequestFailed`, 20

### B

`base` (*darc.link.Link attribute*), 1

### D

`darc`

`module`, 1

`darc.const.CHECK` (*built-in variable*), 16

`darc.const.CHECK_NG` (*built-in variable*), 16

`darc.const.CWD` (*built-in variable*), 16

`darc.const.DARC_CPU` (*built-in variable*), 16

`darc.const.DARC_USER` (*built-in variable*), 16

`darc.const.DARC_WAIT` (*built-in variable*), 18

`darc.const.DB` (*built-in variable*), 17

`darc.const.DEBUG` (*built-in variable*), 15

`darc.const.FLAG_DB` (*built-in variable*), 17

`darc.const.FLAG_MP` (*built-in variable*), 16

`darc.const.FLAG_TH` (*built-in variable*), 16

`darc.const.FORCE` (*built-in variable*), 15

`darc.const.LINK_BLACK_LIST` (*built-in variable*), 18

`darc.const.LINK_FALLBACK` (*built-in variable*), 19

`darc.const.LINK_WHITE_LIST` (*built-in variable*), 18

`darc.const.MIME_BLACK_LIST` (*built-in variable*), 19

`darc.const.MIME_FALLBACK` (*built-in variable*), 19

`darc.const.MIME_WHITE_LIST` (*built-in variable*), 19

`darc.const.PATH_DB` (*built-in variable*), 17

`darc.const.PATH_ID` (*built-in variable*), 17

`darc.const.PATH_LN` (*built-in variable*), 17  
`darc.const.PATH_MISC` (*built-in variable*), 17  
`darc.const.PROXY_BLACK_LIST` (*built-in variable*), 19  
`darc.const.PROXY_FALLBACK` (*built-in variable*), 19  
`darc.const.PROXY_WHITE_LIST` (*built-in variable*), 19  
`darc.const.REBOOT` (*built-in variable*), 15  
`darc.const.REDIS` (*built-in variable*), 17  
`darc.const.ROOT` (*built-in variable*), 16  
`darc.const.SE_EMPTY` (*built-in variable*), 18  
`darc.const.SE_WAIT` (*built-in variable*), 18  
`darc.const.TIME_CACHE` (*built-in variable*), 18  
`darc.const.VERBOSE` (*built-in variable*), 15  
`darc.db.BULK_SIZE` (*built-in variable*), 4  
`darc.db.LOCK_TIMEOUT` (*built-in variable*), 4  
`darc.db.MAX_POOL` (*built-in variable*), 5  
`darc.db.REDIS_LOCK` (*built-in variable*), 5  
`darc.db.REDIS_RETRY` (*built-in variable*), 5  
`darc.error`  
    `module`, 20  
`darc.link`  
    `module`, 1  
`darc.proxy`  
    `module`, 6  
`darc.proxy.bitcoin.LOCK` (*built-in variable*), 6  
`darc.proxy.bitcoin.PATH` (*built-in variable*), 6  
`darc.proxy.data.PATH` (*built-in variable*), 6  
`darc.proxy.ed2k.LOCK` (*built-in variable*), 7  
`darc.proxy.ed2k.PATH` (*built-in variable*), 6  
`darc.proxy.freenet._FREENET_ARGS` (*built-in variable*), 8  
`darc.proxy.freenet._FREENET_BS_FLAG` (*built-in variable*), 8  
`darc.proxy.freenet._FREENET_PROC` (*built-in variable*), 8  
`darc.proxy.freenet._MNG_FREENET` (*built-in variable*), 7  
`darc.proxy.freenet.BS_WAIT` (*built-in variable*), 7  
`darc.proxy.freenet.FREENET_ARGS` (*built-in variable*), 8

variable), 7  
darc.proxy.freenet.FREENET\_PATH (*built-in variable*), 7  
darc.proxy.freenet.FREENET\_PORT (*built-in variable*), 7  
darc.proxy.freenet.FREENET\_RETRY (*built-in variable*), 7  
darc.proxy.i2p.\_I2P\_ARGS (*built-in variable*), 9  
darc.proxy.i2p.\_I2P\_BS\_FLAG (*built-in variable*), 9  
darc.proxy.i2p.\_I2P\_PROC (*built-in variable*), 9  
darc.proxy.i2p.\_MNG\_I2P (*built-in variable*), 9  
darc.proxy.i2p.BS\_WAIT (*built-in variable*), 8  
darc.proxy.i2p.I2P\_ARGS (*built-in variable*), 8  
darc.proxy.i2p.I2P\_PORT (*built-in variable*), 8  
darc.proxy.i2p.I2P\_REQUESTS\_PROXY (*built-in variable*), 8  
darc.proxy.i2p.I2P\_RETRY (*built-in variable*), 8  
darc.proxy.i2p.I2P\_SELENIUM\_PROXY (*built-in variable*), 8  
darc.proxy.irc.LOCK (*built-in variable*), 9  
darc.proxy.irc.PATH (*built-in variable*), 9  
darc.proxy.LINK\_MAP (*in module darc.proxy*), 13  
darc.proxy.magnet.LOCK (*built-in variable*), 9  
darc.proxy.magnet.PATH (*built-in variable*), 9  
darc.proxy.mail.LOCK (*built-in variable*), 9  
darc.proxy.mail.PATH (*built-in variable*), 9  
darc.proxy.null.LOCK (*built-in variable*), 10  
darc.proxy.null.PATH (*built-in variable*), 10  
darc.proxy.script.LOCK (*built-in variable*), 10  
darc.proxy.script.PATH (*built-in variable*), 10  
darc.proxy.tel.LOCK (*built-in variable*), 10  
darc.proxy.tel.PATH (*built-in variable*), 10  
darc.proxy.tor.\_MNG\_TOR (*built-in variable*), 11  
darc.proxy.tor.\_TOR\_BS\_FLAG (*built-in variable*), 11  
darc.proxy.tor.\_TOR\_CONFIG (*built-in variable*), 12  
darc.proxy.tor.\_TOR\_CTRL (*built-in variable*), 12  
darc.proxy.tor.\_TOR\_PROC (*built-in variable*), 11  
darc.proxy.tor.BS\_WAIT (*built-in variable*), 11  
darc.proxy.tor.TOR\_CFG (*built-in variable*), 11  
darc.proxy.tor.TOR\_CTRL (*built-in variable*), 11  
darc.proxy.tor.TOR\_PASS (*built-in variable*), 11  
darc.proxy.tor.TOR\_PORT (*built-in variable*), 11  
darc.proxy.tor.TOR\_REQUESTS\_PROXY (*built-in variable*), 10  
darc.proxy.tor.TOR\_RETRY (*built-in variable*), 11  
darc.proxy.tor.TOR\_SELENIUM\_PROXY (*built-in variable*), 10  
darc.proxy.zeronet.\_MNG\_ZERONET (*built-in variable*), 12  
darc.proxy.zeronet.\_ZERONET\_ARGS (*built-in variable*), 13  
darc.proxy.zeronet.\_ZERONET\_BS\_FLAG (*built-in variable*), 12  
darc.proxy.zeronet.\_ZERONET\_PROC (*built-in variable*), 12  
darc.proxy.zeronet.BS\_WAIT (*built-in variable*), 12  
darc.proxy.zeronet.ZERONET\_ARGS (*built-in variable*), 12  
darc.proxy.zeronet.ZERONET\_PATH (*built-in variable*), 12  
darc.proxy.zeronet.ZERONET\_PORT (*built-in variable*), 12  
darc.proxy.zeronet.ZERONET\_RETRY (*built-in variable*), 12  
darc.save.\_SAVE\_LOCK (*built-in variable*), 4  
darc.sites  
    module, 13  
darc.sites.SITEMAP (*in module darc.sites*), 15  
darc.submit.API\_NEW\_HOST (*built-in variable*), 6  
darc.submit.API\_REQUESTS (*built-in variable*), 6  
darc.submit.API\_RETRY (*built-in variable*), 5  
darc.submit.API\_SELENIUM (*built-in variable*), 6  
darc.submit.PATH\_API (*built-in variable*), 5  
darc.submit.SAVE\_DB (*built-in variable*), 5  
DARC\_BULK\_SIZE, 4  
DARC\_CHECK, 16  
DARC\_CHECK\_CONTENT\_TYPE, 16  
DARC\_CPU, 16  
DARC\_DEBUG, 15  
DARC\_FORCE, 16  
DARC\_LOCK\_TIMEOUT, 4  
DARC\_MAX\_POOL, 5  
DARC\_MULTIPROCESSING, 16  
DARC\_MULTITHREADING, 16  
DARC\_REBOOT, 15, 32  
DARC\_REDIS\_LOCK, 5  
DARC\_REDIS\_RETRY, 5  
DARC\_SAVE, 56  
DARC\_SAVE\_REQUESTS, 56  
DARC\_SAVE\_SELENIUM, 56  
DARC\_USER, 16  
DARC\_VERBOSE, 15  
DARC\_WAIT, 18

## E

environment variable  
    API\_NEW\_HOST, 6, 59  
    API\_REQUESTS, 6, 59  
    API\_RETRY, 6, 59  
    API\_SELENIUM, 6, 59

DARC\_BULK\_SIZE, 4, 55  
 DARC\_CHECK, 16, 53  
 DARC\_CHECK\_CONTENT\_TYPE, 16, 53  
 DARC\_CPU, 16, 54  
 DARC\_DEBUG, 15, 53  
 DARC\_FORCE, 16, 53  
 DARC\_FREEBEE, 63  
 DARC\_I2P, 61  
 DARC\_LOCK\_TIMEOUT, 4  
 DARC\_MAX\_POOL, 5, 55  
 DARC\_MULTIPROCESSING, 16, 54  
 DARC\_MULTITHREADING, 16, 54  
 DARC\_REBOOT, 15, 32, 53  
 DARC\_REDIS\_LOCK, 5  
 DARC\_REDIS\_RETRY, 5  
 DARC\_SAVE, 56  
 DARC\_SAVE\_REQUESTS, 56  
 DARC\_SAVE\_SELENIUM, 56  
 DARC\_TOR, 60  
 DARC\_USER, 16, 54  
 DARC\_VERBOSE, 15, 53  
 DARC\_WAIT, 18, 56  
 DARC\_ZERONET, 62  
 DB\_URL, 55  
 FREEBEE\_ARGS, 63  
 FREEBEE\_PATH, 63  
 FREEBEE\_PORT, 63  
 FREEBEE\_RETRY, 63  
 FREEBEE\_WAIT, 63  
 I2P\_ARGS, 61  
 I2P\_PORT, 61  
 I2P\_RETRY, 61  
 I2P\_WAIT, 61  
 LINK\_BLACK\_LIST, 19, 57  
 LINK\_FALLBACK, 19, 57  
 LINK\_WHITE\_LIST, 18, 57  
 LOCK\_TIMEOUT, 55  
 MIME\_BLACK\_LIST, 19, 58  
 MIME\_FALLBACK, 19, 58  
 MIME\_WHITE\_LIST, 19, 58  
 PATH\_DATA, 17, 54  
 PROXY\_BLACK\_LIST, 19, 58  
 PROXY\_FALLBACK, 20, 58  
 PROXY\_WHITE\_LIST, 19, 58  
 REDIS\_LOCK, 55  
 REDIS\_RETRY, 56  
 REDIS\_URL, 17, 54  
 SAVE\_DB, 5, 59  
 SE\_WAIT, 18, 57  
 TIME\_CACHE, 18, 57  
 TOR\_CFG, 60  
 TOR\_CTRL, 60  
 TOR\_PASS, 60  
 TOR\_PORT, 60  
 TOR\_RETRY, 60  
 TOR\_WAIT, 60  
 ZERONET\_ARGS, 62  
 ZERONET\_PATH, 62  
 ZERONET\_PORT, 62  
 ZERONET\_RETRY, 62  
 ZERONET\_WAIT, 62

**F**  
**G**  
**H**  
**I**  
**L**  
**M**  
**N**  
**P**  
**Q**

*get\_lock () (in module darc.const), 15*  
*host (darc.link.Link attribute), 1*  
*I2PBootstrapFailed, 20*  
*Link (class in darc.link), 1*  
*LINK\_BLACK\_LIST, 19*  
*LINK\_FALLBACK, 19*  
*LINK\_WHITE\_LIST, 18*  
*LinkNoReturn, 20*  
*LockWarning, 20*  
*MIME\_BLACK\_LIST, 19*  
*MIME\_FALLBACK, 19*  
*MIME\_WHITE\_LIST, 19*  
*module*  
*darc, 1*  
*darc.error, 20*  
*darc.link, 1*  
*darc.proxy, 6*  
*darc.sites, 13*  
*name (darc.link.Link attribute), 1*  
*parse\_link () (in module darc.link), 2*  
*PATH\_DATA, 17*  
*proxy (darc.link.Link attribute), 2*  
*PROXY\_BLACK\_LIST, 19*  
*PROXY\_FALLBACK, 20*  
*PROXY\_WHITE\_LIST, 19*  
*quote () (in module darc.link), 3*

## R

REDIS\_URL, 17  
RedisCommandFailed, 20  
render\_error () (*in module darc.error*), 21

## S

SAVE\_DB, 5  
SE\_WAIT, 18  
SiteNotFoundWarning, 21

## T

TIME\_CACHE, 18  
TorBootstrapFailed, 21  
TorRenewFailed, 21

## U

unquote () (*in module darc.link*), 3  
UnsupportedLink, 21  
UnsupportedPlatform, 21  
UnsupportedProxy, 21  
url (*darc.link.Link attribute*), 2  
url\_parse (*darc.link.Link attribute*), 2  
urljoin () (*in module darc.link*), 3  
urlparse () (*in module darc.link*), 4

## Z

ZeroNetBootstrapFailed, 21